

APACHE HD 3MP HD IP CAMERA

*'The
Apache'*



The Apache camera features a water resistance rating to IP66. The camera will operate down to 0-lux, courtesy of 2 High Power nacelle mounted infrared LEDs within a protective glass shield. These IR LEDs automatically trigger-on under low light levels and turn off when suitable levels of light are present. The effective range of the infrared illumination is 70 metres - making the camera ideal for low light-level entrance surveillance, alleyway monitoring, balcony and patio surveillance or any area where suitable covering is unavailable. The camera will also revert to B&W at night utilising the effectiveness of B&W performance in low light conditions. The camera housing is made of a lightweight alloy and is supplied with a swivel mount base and mounting screws. Unit comes complete with 20m of cable and power supply.

SPECIFICATIONS

- Sensor: 1/3" 3MP CMOS IP Camera
- Current Draw: 12vdc 80mA (IR off), 440mA (IR on)
- I/R Range: Up to 70 metres
- RJ45 network interface
- Dual stream
- IP66 Environmental Housing
- Includes CMS Recording Software
- 20cm x 16cm x 8cm in size, Weight: 800g
- Power Over Ethernet
- H.264/MJPEG video compression
- G.726 audio compression (Optional Microphone)
- Supports 32GB SD card
- Supports web browser version
- Multiple protocols: TCP/IP HTTP DHCP
- Supplied with a swivel mount base and 20m of cable and power supply

\$599

(CCTVIPAP)

FOR MORE INFORMATION

42 Botany Rd Alexandria NSW 2015
 PHONE: 1300 130 508 FAX: (02) 9698 5476
www.australsurveillance.com.au
 ABN 85 388 051 001
 MASTER SECURITY LICENCE No. 408916063