2 MegaPixel HD, Indoor / Outdoor Colour IP Camera

2MP **DAY NIGHT** **IP67** **PoE**

Vandal Proof **IR** **ONVIF**

Utilising a 2 Megapixel IP camera, this unit is designed to offer exceptional picture quality indoors and, due to its robust IP67 armoured dome housing, outdoors too! Images can be streamed via network or internet, to a PC or you can even watch from your iPhone! Features include:

Camera
- 2MP IP Camera, ONVIF compliant, 4-9mm Vari-Focal Lens
- Low Illumination Day / Night Chipset , IR Capable to 30m
- IP67 Indoor / Outdoor, Armoured Dome Case
- Includes Basic Recording Software
- Two Way Audio Capable
- PoE or 12 VDC Powered (Power Supply Included)

HD **GeoVision inc**

Image System	
Image sensor	1/3" 2 MP image sensor
Effective pixels	2MP 4:3 1600 (H) X 1200 (V) , 1MP 16:9 1200x720, D1 720x586, CIF 352x288
Image Compression Method	H.264
Frame rate	Frame rate up to 15fps at 1600x1200; up to 30fps at 720x576
Lens	4-9mm Varifocal (Mega pixel lens) 1.5mm fisheye lens is available for option
Electrical	
Audio	Two-way Mono Audio, Full-duplex, G.711 PCM 8kHz (Requires Mic and Speaker connection)
	1 Input / 1 Output
Minimum illumination	0.05 Lux
Feature	
Exposure mode	Auto
White Balance	Auto
Motion detection	5 Motion detection zones
Record mode	Continually, Schedule, Alarm,
Snapshot	Snapshot at local, Snapshot send email or send to FTP
Record	Record at local, record send to FTP server, CMS Compatible
Power Supply	
Power requirement	DC 12V ± 10% / POE 802.3af
Power connector	2.1mm DC Male
Power consumption	Max. 5W
Network	
Ethernet	10Base-T/100Base-TX Ethernet connection for LAN / WAN
Internet protocol	TCP/IP, UDP, HTTP, HTTPs, SMTP, DNS, DHCP, NTP, FTP, RTP,RTSP, ICMP, uPNP, RSTP
IP	IPv4
Connectors	RJ-45
Browser	IE browser 6.0 or above
Audio In / Out port	YES, 1 Input / 1 Output
Mechanical	
Dimensions(L x W x H)	151.69 x 114.9mm IP67 Armoured Dome Housing
Weight	1.1kg

$299 CCTV08HRDNIP

www.australsurveillance.com.au

1300 130 508

Celebrating **20** years 1997-2017